

DAFTAR PUSTAKA

- [1] M. F. Praevia and W. Widayat, "Analisis Pemanfaatan Limbah Tandan Kosong Kelapa Sawit Sebagai Cofiring pada PLTU Batubara," *J. Energi Baru dan Terbarukan*, vol. 3, no. 1, pp. 28–37, 2022, doi: 10.14710/jebt.2022.13367.
- [2] I. Nyoman, S. Winaya, I. B. Agung, and D. Susila, "Co-Firing Sistem Fludized Bed Berbahan Bakar Batubara dan Ampas Tebu," *J. Ilm. Tek. Mesin*, vol. 4, no. 2, pp. 180–188, 2010.
- [3] R. Kabir Ahmad, S. Anwar Sulaiman, S. Yusup, S. Sham Dol, M. Inayat, and H. Aminu Umar, "Exploring the potential of coconut shell biomass for charcoal production," *Ain Shams Eng. J.*, vol. 13, no. 1, p. 101499, 2022, doi: <https://doi.org/10.1016/j.asej.2021.05.013>.
- [4] K. E. Anyaoha, R. Sakrabani, K. Patchigolla, and A. M. Mouazen, "Critical evaluation of oil palm fresh fruit bunch solid wastes as soil amendments: Prospects and challenges," *Resour. Conserv. Recycl.*, vol. 136, pp. 399–409, 2018, doi: <https://doi.org/10.1016/j.resconrec.2018.04.022>.
- [5] Y. Niu, H. Tan, and S. Hui, "Ash-related issues during biomass combustion: Alkali-induced slagging, silicate melt-induced slagging (ash fusion), agglomeration, corrosion, ash utilization, and related countermeasures," *Prog. Energy Combust. Sci.*, vol. 52, pp. 1–61, 2016, doi: <https://doi.org/10.1016/j.pecs.2015.09.003>.
- [6] M. Hupa, O. Karlström, and E. Vainio, "Biomass combustion technology development – It is all about chemical details," *Proc. Combust. Inst.*, vol. 36, no. 1, pp. 113–134, 2017, doi: <https://doi.org/10.1016/j.proci.2016.06.152>.
- [7] O. Karlström, M. Perander, N. DeMartini, A. Brink, and M. Hupa, "Role of ash on the NO formation during char oxidation of biomass," *Fuel*, vol. 190, pp. 274–280, 2017, doi: <https://doi.org/10.1016/j.fuel.2016.11.013>.
- [8] S. V Vassilev, D. Baxter, L. K. Andersen, and C. G. Vassileva, "An overview of the chemical composition of biomass," *Fuel*, vol. 89, no. 5, pp.

913–933, 2010, doi: <https://doi.org/10.1016/j.fuel.2009.10.022>.

- [9] A. Singhal, J. Konttinen, and T. Joronen, “Effect of different washing parameters on the fuel properties and elemental composition of wheat straw in water-washing pre-treatment. Part 2: Effect of washing temperature and solid-to-liquid ratio,” *Fuel*, vol. 292, p. 120209, 2021, doi: <https://doi.org/10.1016/j.fuel.2021.120209>.
- [10] A. Prismantoko, Y. Heryana, Y. Peryoga, and A. Wijono, “Reduksi Kandungan Kalium Tandan Kosong Kelapa Sawit Dengan Pencucian Metoda Aliran Air,” *Semin. Nas. Sains dan Teknol. 2017*, no. November, pp. 1–5, 2017.
- [11] P. Y. Lam *et al.*, “Leaching Characteristics of Inorganic Constituents from Oil Palm Residues by Water,” *Ind. & Eng. Chem. Res.*, vol. 53, no. 29, pp. 11822–11827, 2014, doi: 10.1021/ie500769s.
- [12] C. Tan, K. Saritpongteeraka, S. Kungsanant, B. Charnnok, and S. Chaiprapat, “Low temperature hydrothermal treatment of palm fiber fuel for simultaneous potassium removal, enhanced oil recovery and biogas production,” *Fuel*, vol. 234, pp. 1055–1063, 2018, doi: <https://doi.org/10.1016/j.fuel.2018.07.137>.
- [13] K. L. Chin *et al.*, “Reducing ash related operation problems of fast growing timber species and oil palm biomass for combustion applications using leaching techniques,” *Energy*, vol. 90, pp. 622–630, 2015, doi: <https://doi.org/10.1016/j.energy.2015.07.094>.
- [14] L. C. H. Solorzano, C. A. F. Nuñez, and F. E. Sierra-Vargas, “Biomass densification: A review of the current state-of-the-art of the pellet market and analysis of new research trends,” *Tecciencia*, vol. 12, no. 23, pp. 81–92, 2017.
- [15] W. B. Kusumaningrum and S. S. Munawar, “Prospect of bio-pellet as an alternative energy to substitute solid fuel based,” *Energy Procedia*, vol. 47, pp. 303–309, 2014, doi: 10.1016/j.egypro.2014.01.229.
- [16] A. Nurdawati, S. Novianti, I. N. Zaini, H. Sumida, and K. Yoshikawa, “Production of low-potassium Solid Fuel from empty fruit bunches (EFB)

- by employing hydrothermal treatment and water washing process,” *Nihon Enerugi Gakkaishi/Journal Japan Inst. Energy*, vol. 94, no. 8, pp. 775–780, 2015, doi: 10.3775/jie.94.775.
- [17] D. PPHP, “Pedoman Pengelolaan Limbah Industri Kelapa Sawit. Subdit Pengelolaan Lingkungan Direktorat Pengelohan Hasil Pertanian,” Jakarta, 2006.
 - [18] P. Rama Rao and G. Ramakrishna, “Oil palm empty fruit bunch fiber: surface morphology, treatment, and suitability as reinforcement in cement composites- A state of the art review,” *Clean. Mater.*, vol. 6, no. April, p. 100144, 2022, doi: 10.1016/j.clema.2022.100144.
 - [19] M. S. Sreekala, M. G. Kumaran, and S. Thomas, “Oil palm fibers: Morphology, chemical composition, surface modification, and mechanical properties,” *J. Appl. Polym. Sci.*, vol. 66, no. 5, pp. 821–835, 1997, doi: 10.1002/(sici)1097-4628(19971031)66:5<821::aid-app2>3.0.co;2-x.
 - [20] B. M. Jenkins, R. R. Bakker, and J. B. Wei, “On the properties of washed straw,” *Biomass and Bioenergy*, vol. 10, no. 4, pp. 177–200, 1996, doi: 10.1016/0961-9534(95)00058-5.
 - [21] H. M. Westberg, M. Byström, and B. Leckner, “Distribution of potassium, chlorine, and sulfur between solid and vapor phases during combustion of wood chips and coal,” *Energy and Fuels*, vol. 17, no. 1, pp. 18–28, 2003, doi: 10.1021/ef020060l.
 - [22] N. Abdullah and H. Gerhauser, “Bio-oil derived from empty fruit bunches,” *Fuel*, vol. 87, no. 12, pp. 2606–2613, 2008, doi: 10.1016/j.fuel.2008.02.011.
 - [23] P. Das, A. Ganesh, and P. Wangikar, “Influence of pretreatment for deashing of sugarcane bagasse on pyrolysis products,” *Biomass and Bioenergy*, vol. 27, no. 5, pp. 445–457, 2004, doi: 10.1016/j.biombioe.2004.04.002.
 - [24] K. O. Davidsson, J. G. Korsgren, J. B. C. Pettersson, and U. Jäglid, “The effects of fuel washing techniques on alkali release from biomass,” *Fuel*, vol. 81, no. 2, pp. 137–142, 2002, doi: 10.1016/S0016-2361(01)00132-6.
 - [25] M. A. Jensen, A., Dam-Johansen, K., Wójtowicz, M. A., & Serio, “TG-

- FTIR study of the influence of potassium chloride on wheat straw pyrolysis,” *Energy and Fuels*, vol. 12, no. 5, pp. 929–938, 1998, doi: <https://doi.org/10.1021/ef980008i>.
- [26] W. Zhu, W. Song, and W. Lin, “Catalytic gasification of char from co-pyrolysis of coal and biomass,” *Fuel Process. Technol.*, vol. 89, no. 9, pp. 890–896, 2008, doi: 10.1016/j.fuproc.2008.03.001.
- [27] N. Abdullah and F. Sulaiman, “The properties of the washed empty fruit bunches of oil palm,” *J. Phys. Sci.*, vol. 24, no. 2, pp. 117–137, 2013.
- [28] L. J. . Nunes, J. C. . Matias, and J. P. . Catalao, “A review on torrefied biomass pellets as a sustainable alternative to coal in power generation,” *Renewable Sustain. Energy Rev.*, vol. 40, pp. 153–160, 2014, doi: <http://dx.doi.org/10.1016/j.rser.2014.07.181>.
- [29] P. Basu, *Biomass Gasification, Pyrolysis and Torrefaction: Practical Design and Theory*, Second Edi. Elsevier Inc., 2013. doi: 10.1016/C2011-0-07564-6.
- [30] A. Setiawan, F. Hayat, Faisal, and T. B. Nur, “Combustion characteristics of densified bio-char produced from Gayo Arabica coffee-pulp: Effect of binder,” *IOP Conf. Ser. Earth Environ. Sci.*, vol. 364, no. 1, 2019, doi: 10.1088/1755-1315/364/1/012007.
- [31] P. Pradhan, S. M. Mahajani, and A. Arora, “Production and utilization of fuel pellets from biomass: A review,” *Fuel Process. Technol.*, vol. 181, no. August, pp. 215–232, 2018, doi: 10.1016/j.fuproc.2018.09.021.
- [32] T. Yulianto, “Pengaruh Torefaksi Terhadap Sifat Fisis Black Pellet Tandan Kosong Kelapa Sawit (TKKS),” Universitas Lampung Bandar, Lampung., 2020.
- [33] Amirta Rudianto, *Pellet kayu*, Juli 2018. Samarinda – Kalimantan Timur – Indonesia 75123: Mulawarman University PRESS. Samarinda – Kalimantan Timur, 2018.
- [34] M. Jufri, I. Farosadid, Mulyono, and A. Mokhtar, “Analisis variasi temperatur pengeringan dan persentase perekat terhadap lama waktu pembakaran biopellet sekam padi,” *Semin. Nas. Teknol. dan Rekayasa 2018*,

pp. 96–99, 2018.

- [35] J. Asri, M., Kurniawan, E., Sylvia, N., Bahri, S., dan Jalaluddin, “Pemanfaatan Limbah Sekam Padi Sebagai Bahan Alternatif Dalam Pembuatan Biopellet,” *Chem. Eng. J. Storage*, vol. 2, no. 2, p. 57, 2022, doi: <https://doi.org/10.29103/cejs.v2i2.7232>.
- [36] F. Huseini, Solihin, and Pramusanto, “Kajian Kualitas Batubara Berdasarkan Analisis Proksimat, Total Sulfur dan Nilai Kalor Untuk Pembakaran Bahan Baku Semen di PT Semen Padang Kelurahan Batu Gadang, Kecamatan Lubuk Kilangan, Kota Padang Provinsi Sumatera Barat,” *Pros. Tek. Pertamb.*, vol. 4, no. 2, pp. 668–677, 2018.
- [37] Y. A. Almu, M. A., Syahrul, S., dan Padang, “Analisa nilai kalor dan laju pembakaran pada briket campuran biji nyamplung (*calophyllum inophyllum*) dan abu sekam padi,” *Din. Tek. Mesin*, vol. 4, no. 2, pp. 117–122, 2014, doi: <https://doi.org/10.29303/d.v4i2.61>.
- [38] D. Chen, J. Zhou, Q. Zhang, X. Zhu, and Q. Lu, “Upgrading of rice husk by torrefaction and its influence on the fuel properties,” *BioResources*, vol. 9, no. 4, pp. 5893–5905, 2014, doi: 10.15376/biores.9.4.5893-5905.
- [39] A. Setiabudi, R. Hardian, and A. Muzakir, *Karakterisasi Material: Prinsip dan Aplikasinya dalam Penelitian Kimia*, vol. 1. 2012.
- [40] C. Setter, F. A. Borges, C. R. Cardoso, R. F. Mendes, and T. J. P. Oliveira, “Energy quality of pellets produced from coffee residue: Characterization of the products obtained via slow pyrolysis,” *Ind. Crops Prod.*, vol. 154, Oct. 2020, doi: 10.1016/j.indcrop.2020.112731.
- [41] C. Setter, F. A. Borges, C. R. Cardoso, R. F. Mendes, and T. J. P. Oliveira, “Energy quality of pellets produced from coffee residue: Characterization of the products obtained via slow pyrolysis,” *Ind. Crops Prod.*, vol. 154, no. October 2019, p. 112731, 2020, doi: 10.1016/j.indcrop.2020.112731.
- [42] F. Sihombing, L. Siregar, A. N. Sibarani, “Studi Analisis Perubahan Motor Induksi 1 Fasa Akibat Output PLTS Aplikasi Kipas Angin,” *Elpotecs Jurnal* Vol. 3. 2020.