

DAFTAR PUSTAKA

- [1] W. H. Chen, K. M. Lu, S. H. Liu, C. M. Tsai, W. J. Lee, and T. C. Lin, "Biomass torrefaction characteristics in inert and oxidative atmospheres at various superficial velocities," *Bioresour Technol*, vol. 146, pp. 152–160, 2013, doi: 10.1016/j.biortech.2013.07.064.
- [2] M. Safar *et al.*, "Catalytic effects of potassium on biomass pyrolysis, combustion and torrefaction," *Appl Energy*, vol. 235, pp. 346–355, Feb. 2019, doi: 10.1016/j.apenergy.2018.10.065.
- [3] K. Tim *et al.*, "Pedoman Teknis Pengelolaan Limbah Industri Kecil."
- [4] X. Wang *et al.*, "Thermogravimetric kinetic study of agricultural residue biomass pyrolysis based on combined kinetics," *Bioresour Technol*, vol. 219, pp. 510–520, Nov. 2016, doi: 10.1016/j.biortech.2016.07.136.
- [5] P. S. Lam, S. Sokhansanj, X. T. Bi, C. J. Lim, and S. H. Larsson, "Drying characteristics and equilibrium moisture content of steam-treated Douglas fir (*Pseudotsuga menziesii* L.)," *Bioresour Technol*, vol. 116, pp. 396–402, Jul. 2012, doi: 10.1016/j.biortech.2012.03.093.
- [6] G. W. Huber, S. Iborra, and A. Corma, "Synthesis of transportation fuels from biomass: Chemistry, catalysts, and engineering," *Chemical Reviews*, vol. 106, no. 9, pp. 4044–4098, Sep. 2006. doi: 10.1021/cr068360d.
- [7] J. G. Lynam, C. J. Coronella, W. Yan, M. T. Reza, and V. R. Vasquez, "Acetic acid and lithium chloride effects on hydrothermal carbonization of lignocellulosic biomass," *Bioresour Technol*, vol. 102, no. 10, pp. 6192–6199, 2011, doi: 10.1016/j.biortech.2011.02.035.
- [8] W. Yan, J. T. Hastings, T. C. Acharjee, C. J. Coronella, and V. R. Vásquez, "Mass and energy balances of wet torrefaction of lignocellulosic biomass," in *Energy and Fuels*, Sep. 2010, pp. 4738–4742. doi: 10.1021/ef901273n.
- [9] H. C. Ong *et al.*, "Variation of lignocellulosic biomass structure from torrefaction: A critical review," *Renewable and Sustainable Energy Reviews*, vol. 152, Dec. 2021, doi: 10.1016/j.rser.2021.111698.
- [10] W. H. Chen *et al.*, "Progress in biomass torrefaction: Principles, applications and challenges," *Progress in Energy and Combustion Science*, vol. 82. Elsevier Ltd, Jan. 01, 2021. doi: 10.1016/j.pecs.2020.100887.
- [11] M. Phanphanich and S. Mani, "Impact of torrefaction on the grindability and fuel characteristics of forest biomass," *Bioresour Technol*, vol. 102, no. 2, pp. 1246–1253, Jan. 2011, doi: 10.1016/j.biortech.2010.08.028.

- [12] M. Manouchehrinejad, E. M. T. Bilek, and S. Mani, “Techno-economic analysis of integrated torrefaction and pelletization systems to produce torrefied wood pellets,” *Renew Energy*, vol. 178, pp. 483–493, Nov. 2021, doi: 10.1016/j.renene.2021.06.064.
- [13] J. Poudel, T. I. Ohm, and S. C. Oh, “A study on torrefaction of food waste,” *Fuel*, vol. 140, pp. 275–281, Jan. 2015, doi: 10.1016/j.fuel.2014.09.120.
- [14] B. Ghiasi *et al.*, “Densified biocoal from woodchips: Is it better to do torrefaction before or after densification?,” *Appl Energy*, vol. 134, pp. 133–142, Dec. 2014, doi: 10.1016/j.apenergy.2014.07.076.
- [15] J. J. Chew and V. Doshi, “Recent advances in biomass pretreatment - Torrefaction fundamentals and technology,” *Renewable and Sustainable Energy Reviews*, vol. 15, no. 8. Elsevier Ltd, pp. 4212–4222, 2011. doi: 10.1016/j.rser.2011.09.017.
- [16] M. A. Brand, T. Mariano Rodrigues, J. Peretti da Silva, and J. de Oliveira, “Recovery of agricultural and wood wastes: The effect of biomass blends on the quality of pellets,” *Fuel*, vol. 284, Jan. 2021, doi: 10.1016/j.fuel.2020.118881.
- [17] M. Holubcik, R. Nosek, and J. Jandacka, “Optimization of the Production Process of Wood Pellets by Adding Additives,” *International Journal of Energy Optimization and Engineering*, vol. 1, no. 2, pp. 20–40, Apr. 2012, doi: 10.4018/ijeoe.2012040102.
- [18] J. Peng *et al.*, “Sawdust as an effective binder for making torrefied pellets,” *Appl Energy*, vol. 157, pp. 491–498, 2015, doi: 10.1016/j.apenergy.2015.06.024.
- [19] P. Basu, *Biomass Gasification, Pyrolysis and Torrefaction: Practical Design and Theory*. 2013. doi: 10.1016/C2011-0-07564-6.
- [20] A. Tursi, “A review on biomass: Importance, chemistry, classification, and conversion,” *Biofuel Research Journal*, vol. 6, no. 2, pp. 962–979, 2019, doi: 10.18331/BRJ2019.6.2.3.
- [21] R. Gürel, “Torrefaction of Biomass,” no. August, 2011.
- [22] W. H. Chen, H. J. Hsu, G. Kumar, W. M. Budzianowski, and H. C. Ong, “Predictions of biochar production and torrefaction performance from sugarcane bagasse using interpolation and regression analysis,” *Bioresour Technol*, vol. 246, pp. 12–19, 2017, doi: 10.1016/j.biortech.2017.07.184.

- [23] J. S. Tumuluru, R. D. Boardman, C. T. Wright, and J. R. Hess, "Some chemical compositional changes in miscanthus and white oak sawdust samples during torrefaction," *Energies (Basel)*, vol. 5, no. 10, pp. 3928–3947, 2012, doi: 10.3390/en5103928.
- [24] L. Shang, "Upgrading Fuel Properties of Biomass by Torrefaction," *Ph.D.*, p. 146, 2012.
- [25] Q.-V. Bach, *Wet Torrefaction of Biomass – Production and Conversion of Hydrochar*. 2015.
- [26] "© Idris O. Sule, August, 2012," 2012.
- [27] B. S. Dien *et al.*, "Chemical composition and response to dilute-acid pretreatment and enzymatic saccharification of alfalfa, reed canarygrass, and switchgrass," *Biomass Bioenergy*, vol. 30, no. 10, pp. 880–891, 2006, doi: 10.1016/j.biombioe.2006.02.004.
- [28] R. E. S. Purba, Irwan, and Nurmaidah, "Utilization of Wood Sawdust Waste As a Mixed Substitution of Soft Mixed Brick," *JCEBT (Journal of Civil Engineering, Building and Transportation)*, vol. 1, no. 2, pp. 87–95, 2017.
- [29] M. Wijaya, E. Noor, T. T. Irawadi, and G. Pari, "Pyrolysis Temperature Change at Chemical Wood Vinegar Component from Pine Wood Sawdust," *Jurnal Ilmu dan Teknologi Hasil Hutan*, vol. 1, no. 2, pp. 73–77, 2008.
- [30] M. Billah, *Briket Bab 1 Ambil*.
- [31] J. Penelitian, K. Pembakaran, B. Arang, E. Gondok, and E. Gondok, "KINETIKA PEMBAKARAN BRIKET ARANG ENCENG GONDOK Elly Kurniati dan Suprihatin Teknik Kimia , FTI UPN ‘ Veteran ’ Jatim Intisari," vol. 9, no. 1, pp. 70–77, 2009.
- [32] G. A. Arini and S. Aminah, "Pemanfaatan Serbuk Gergaji Kayu Jati (Tectona Grandis L.F) Sebagai Adsorben Logam Cu (Ii)," *Media Eksakta*, vol. 16, no. 2, pp. 89–97, 2020, doi: 10.22487/me.v16i2.739.
- [33] J. L. Espinoza-Acosta, P. I. Torres-Chávez, E. Carvajal-Millán, B. Ramírez-Wong, L. A. Bello-Pérez, and B. Montaña-Leyva, "Ionic liquids and organic solvents for recovering lignin from lignocellulosic biomass," *Bioresources*, vol. 9, no. 2, pp. 3660–3687, 2014, doi: 10.15376/biores.9.2.3660-3687.
- [34] P. Parthasarathy and S. K. Narayanan, "Effect of Hydrothermal Carbonization Reaction Parameters on," *Environ Prog Sustain Energy*, vol. 33, no. 3, pp. 676–680, 2014, doi: 10.1002/ep.

- [35] S. Nizamuddin, N. M. Mubarak, M. Tiripathi, N. S. Jayakumar, J. N. Sahu, and P. Ganesan, "Chemical, dielectric and structural characterization of optimized hydrochar produced from hydrothermal carbonization of palm shell," *Fuel*, vol. 163, no. September, pp. 88–97, 2016, doi: 10.1016/j.fuel.2015.08.057.
- [36] L. Zhan, Q. Wang, B. Wang, G. Yang, L. A. Lucia, and J. Chen, "Hydrothermal Carbonization of Corncob Residues for Hydrochar Production," *Energy Fuels*, vol. 29, no. 2, pp. 872–876, 2015, doi: <https://doi.org/10.1021/ef502462p>.
- [37] S. Wang, G. Dai, H. Yang, and Z. Luo, "Lignocellulosic biomass pyrolysis mechanism: A state-of-the-art review," *Prog Energy Combust Sci*, vol. 62, pp. 33–86, 2017, doi: 10.1016/j.peccs.2017.05.004.
- [38] A. Ignatiev, X. Chen, N. Wu, Z. Lu, and L. Smith, "Nanostructured thin solid oxide fuel cells with high power density," *Dalton Transactions*, vol. 9226, no. 40, pp. 5501–5506, 2008, doi: 10.1039/b805658g.
- [39] N. Y. Othmer Kirk. "Encyclopedia of Chemical Technology vol. 23", 3ed McGraw-Hill Book Company Inc., "No Title".
- [40] *Perrys Chemical Engineering Handbook 7th Edition Price*. 1999.
- [41] A. M. J. Kootstra, H. H. Beeftink, E. L. Scott, and J. P. M. Sanders, "Comparison of dilute mineral and organic acid pretreatment for enzymatic hydrolysis of wheat straw," *Biochem Eng J*, vol. 46, no. 2, pp. 126–131, 2009, doi: 10.1016/j.bej.2009.04.020.
- [42] M. Cremers, J. Koppejan, S. Sokhansanj, S. Melin, and S. Madrali, *Status overview of torrefaction technologies*. 2015.
- [43] A. Uslu, A. P. C. Faaij, and P. C. A. Bergman, "Pre-treatment technologies, and their effect on international bioenergy supply chain logistics. Techno-economic evaluation of torrefaction, fast pyrolysis and pelletisation," *Energy*, vol. 33, no. 8, pp. 1206–1223, 2008, doi: 10.1016/j.energy.2008.03.007.
- [44] Y. Chen, B. Liu, H. Yang, Q. Yang, and H. Chen, "Evolution of functional groups and pore structure during cotton and corn stalks torrefaction and its correlation with hydrophobicity," *Fuel*, vol. 137, pp. 41–49, 2014, doi: 10.1016/j.fuel.2014.07.036.
- [45] J. Zhang, T. Chen, J. Wu, and J. Wu, "Multi-Gaussian-DAEM-reaction model for thermal decompositions of cellulose, hemicellulose and lignin: Comparison of N₂ and CO₂ atmosphere," *Bioresour Technol*, vol. 166, pp. 87–95, 2014, doi: 10.1016/j.biortech.2014.05.030.

- [46] W. H. Chen *et al.*, “Progress in biomass torrefaction: Principles, applications and challenges,” *Prog Energy Combust Sci*, vol. 82, 2021, doi: 10.1016/j.pecs.2020.100887.
- [47] C. Wang *et al.*, “Oxidative torrefaction of biomass residues and densification of torrefied sawdust to pellets,” *Bioresour Technol*, vol. 127, pp. 318–325, 2013, doi: 10.1016/j.biortech.2012.09.092.
- [48] W. Yan, T. C. Acharjee, C. J. Coronella, and V. R. Vásquez, “Thermal pretreatment of lignocellulosic biomass,” *Environ Prog Sustain Energy*, vol. 28, no. 3, pp. 435–440, Oct. 2009, doi: 10.1002/ep.10385.
- [49] Q. V. Bach and O. Skreiberg, “Upgrading biomass fuels via wet torrefaction: A review and comparison with dry torrefaction,” *Renewable and Sustainable Energy Reviews*, vol. 54, pp. 665–677, 2016, doi:10.1016/j.rser.2015.10.014.
- [50] W. Yan, J. T. Hastings, T. C. Acharjee, C. J. Coronella, and V. R. Vásquez, “Mass and energy balances of wet torrefaction of lignocellulosic biomass,” *Energy and Fuels*, vol. 24, no. 9, pp. 4738–4742, 2010, doi: 10.1021/ef901273n.
- [51] N. Shi, Q. Liu, H. Cen, R. Ju, X. He, and L. Ma, “Formation of humins during degradation of carbohydrates and furfural derivatives in various solvents,” *Biomass Convers Biorefin*, vol. 10, no. 2, pp. 277–287, 2020, doi: 10.1007/s13399-019-00414-4.
- [52] B. Columbia and B. Columbia, “Updates on Softwood-to-Ethanol Process,” vol. 129, 2006.
- [53] P. S. Lam, S. Sokhansanj, X. Bi, C. J. Lim, and S. Melin, “Energy input and quality of pellets made from steam-exploded douglas fir (*Pseudotsuga menziesii*),” *Energy and Fuels*, vol. 25, no. 4, pp. 1521–1528, 2011, doi: 10.1021/ef101683s.
- [54] Z. Tooyserkani *et al.*, “Effect of steam treatment on pellet strength and the energy input in pelleting of softwood particles,” *Trans ASABE*, vol. 55, no. 6, pp. 2265–2272, 2012, doi: 10.13031/2013.42484.
- [55] P. Rousset, C. Aguiar, N. Labbé, and J. M. Commandré, “Enhancing the combustible properties of bamboo by torrefaction,” *Bioresour Technol*, vol. 102, no. 17, pp. 8225–8231, 2011, doi: 10.1016/j.biortech.2011.05.093.
- [56] J. Wannapeera, B. Fungtammasan, and N. Worasuwannarak, “Effects of temperature and holding time during torrefaction on the pyrolysis behaviors of woody biomass,” *J Anal Appl Pyrolysis*, vol. 92, no. 1, pp. 99–105, 2011, doi: 10.1016/j.jaap.2011.04.010.

- [57] S. S. Thanapal, W. Chen, K. Annamalai, N. Carlin, R. J. Ansley, and D. Ranjan, "Carbon dioxide torrefaction of woody biomass," *Energy and Fuels*, vol. 28, no. 2, pp. 1147–1157, 2014, doi: 10.1021/ef4022625.
- [58] S. Barskov *et al.*, "Torrefaction of biomass: A review of production methods for biocoal from cultured and waste lignocellulosic feedstocks," *Renew Energy*, vol. 142, pp. 624–642, 2019, doi: 10.1016/j.renene.2019.04.068.
- [59] M. Asadullah, A. M. Adi, N. Suhada, N. H. Malek, M. I. Saringat, and A. Azdarpour, "Optimization of palm kernel shell torrefaction to produce energy densified bio-coal," *Energy Convers Manag*, vol. 88, pp. 1086–1093, 2014, doi: 10.1016/j.enconman.2014.04.071.
- [60] M. Zabeti, T. S. Nguyen, L. Lefferts, H. J. Heeres, and K. Seshan, "In situ catalytic pyrolysis of lignocellulose using alkali-modified amorphous silica alumina," *Bioresour Technol*, vol. 118, pp. 374–381, 2012, doi: 10.1016/j.biortech.2012.05.034.
- [61] S. B. Saleh, B. B. Hansen, P. A. Jensen, and K. Dam-Johansen, "Influence of biomass chemical properties on torrefaction characteristics," *Energy and Fuels*, vol. 27, no. 12, pp. 7541–7548, 2013, doi: 10.1021/ef401788m.
- [62] T. Khazraie Shoulaifar, N. Demartini, O. Karlström, and M. Hupa, "Impact of organically bonded potassium on torrefaction: Part 1. Experimental," *Fuel*, vol. 165, pp. 544–552, 2016, doi: 10.1016/j.fuel.2015.06.024.
- [63] M. Holubcik, R. Nosek, and J. Jandacka, "Optimization of the Production Process of Wood Pellets by Adding Additives," *International Journal of Energy Optimization and Engineering*, vol. 1, no. 2, pp. 20–40, 2012, doi: 10.4018/ijeoe.2012040102.
- [64] Amirta Rudianto, "Pellet kayu," p. 81, 2018.
- [65] R. Alamsyah, N. C. Siregar, and F. Hasanah, "Peningkatan Nilai Kalor Pellet Biomassa Cocopeat sebagai Bahan Bakar Terbarukan dengan Aplikasi Torefaksi," *Warta Industri Hasil Pertanian*, vol. 33, no. 01, pp. 17–23, 2018.
- [66] F. Fantozzi and C. Buratti, "Life cycle assessment of biomass chains: Wood pellet from short rotation coppice using data measured on a real plant," *Biomass Bioenergy*, vol. 34, no. 12, pp. 1796–1804, 2010, doi: 10.1016/j.biombioe.2010.07.011.
- [67] P. Lehtikangas, "Quality properties of pelletised sawdust, logging residues and bark," *Biomass Bioenergy*, vol. 20, no. 5, pp. 351–360, 2001, doi: 10.1016/S0961-9534(00)00092-1.
- [68] S. N. Indonesia, "Pelet biomassa untuk pembangkit listrik," 2020.

- [69] T. Yulianto, "Pengaruh Torefaksi Terhadap Sifat Fisis Black Pellet Tandan Kosong Kelapa Sawit (TKKS)," 2020.
- [70] A. A. Siyal *et al.*, "Torrefaction subsequent to pelletization: Characterization and analysis of furfural residue and sawdust pellets," *Waste Management*, vol. 113, pp. 210–224, 2020, doi: 10.1016/j.wasman.2020.05.037.
- [71] P. Alizadeh, L. G. Tabil, P. K. Adapa, D. Cree, E. Mupondwa, and B. Emadi, "Torrefaction and Densification of Wood Sawdust for Bioenergy Applications," *Fuels*, vol. 3, no. 1, pp. 152–175, 2022, doi: 10.3390/fuels3010010.
- [72] Q. V. Bach, K. Q. Tran, R. A. Khalil, Ø. Skreiberg, and G. Seisenbaeva, "Comparative assessment of wet torrefaction," *Energy and Fuels*, vol. 27, no. 11, pp. 6743–6753, 2013, doi: 10.1021/ef401295w.
- [73] M. J. Gan *et al.*, "Enhancement of Palm Kernel Shell Fuel Properties via Wet Torrefaction: Response Surface, Optimization, and Combustion Studies," *Energy and Fuels*, 2019, doi: 10.1021/acs.energyfuels.9b02229.
- [74] R. Andrew Setiawan, "Kajian Potensi Penggunaan By Product Industri Pertanian Di Kabupaten Jember Sebagai Bahan Baku Pembuatan Biopellet Untuk Bahan Bakar Alternatif," *Agrointek*, vol. 8, no. 1, pp. 8–12, 2014.
- [75] M. F. Mahdie, D. Subari, Sunardi, and D. Ulfah, "Pengaruh Campuran Limbah Kayu Rambai Dan Api-Api Terhadap Kualitas Biopellet Sebagai Energi Alternatif Dari Lahan Basah," *Jurnal Hutan Tropis*, vol. 4, no. 3, pp. 246–253, 2016.
- [76] A. Setiawan, F. Hayat, Faisal, and T. B. Nur, "Combustion characteristics of densified bio-char produced from Gayo Arabica coffee-pulp: Effect of binder," *IOP Conf Ser Earth Environ Sci*, vol. 364, no. 1, 2019, doi: 10.1088/1755-1315/364/1/012007.
- [77] W. Hidayat, Y. Qi, J. H. Jang, F. Febrianto, S. H. Lee, and N. H. Kim, "Heat-treated okan wood," *Bioresources*, vol. 11, no. 4, pp. 10070–10086, 2016, [Online]. Available: https://ojs.cnr.ncsu.edu/index.php/BioRes/article/view/BioRes_11_4_10070_Hidayat_Duration_Clamping_Okan_Wood
- [78] D. Hendra, "Rekayasa Pembuatan Mesin Pelet Kayu Dan Pengujian Hasilnya (Design and Manufacture of Wood Pellets Machine and Testing of its Product)," *Jurnal Penelitian Hasil Hutan*, vol. 30, no. 2, pp. 144–154, 2012.

- [79] I. Obernberger and G. Thek, “Physical characterisation and chemical composition of densified biomass fuels with regard to their combustion behaviour,” *Biomass Bioenergy*, vol. 27, no. 6, pp. 653–669, 2004, doi: 10.1016/j.biombioe.2003.07.006.
- [80] I. S. Mohammed, R. Na, K. Kushima, and N. Shimizu, “Investigating the effect of processing parameters on the products of hydrothermal carbonization of corn stover,” *Sustainability (Switzerland)*, vol. 12, no. 12, 2020, doi: 10.3390/su12125100.
- [81] G. Pari, D. Tohir, and J. Ferry, “ADSORBEN PADA PEMURNIAN MINYAK GORENG BEKAS (Activated Charcoal from Wood Sawdust as Adsorbent Material for Frying Oil Refinery)”.
- [82] M. F. Li, Y. Shen, J. K. Sun, J. Bian, C. Z. Chen, and R. C. Sun, “Wet Torrefaction of Bamboo in Hydrochloric Acid Solution by Microwave Heating,” *ACS Sustain Chem Eng*, vol. 3, no. 9, pp. 2022–2029, 2015, doi: 10.1021/acssuschemeng.5b00296.
- [83] E. Wibowo Kurniawan, “Studi Karakteristik Briket Tempurung Kelapa dengan Berbagai Jenis Perekat Briket,” *Buletin Loupe*, vol. 15, no. 01, p. 7, 2019, doi: 10.51967/buletinloupe.v15i01.24.
- [84] N. Arifin and D. R. Noor, “PENGARUH KOMPOSISI CAMPURAN BRIKET ARANG ALANG-ALANG (IMPERATA CYLINDRICA) UNTUK MENINGKATKAN NILAI KALOR EFFECT OF COMPOSITION THE MIXTURE OF CHARCOAL BRIQUETTES MADE FROM REEDS (IMPERATA CYLINDRICA) TO INCREASE CALORY VALUE,” 2016.
- [85] Subroto, T. Tjahjono, and A. MKR, “Pengaruh Variasi Komposisi Biobri,” vol. 17, no. 1, pp. 34–43, 2016.
- [86] A. Dyjakon, T. Noszczyk, and M. Smędzik, “The influence of torrefaction temperature on hydrophobic properties of waste biomass from food processing,” *Energies (Basel)*, vol. 12, no. 24, 2019, doi: 10.3390/en12244609.
- [87] F. J. Polnaya, H. Hilda, and C. G. C. Lopulalan, “Konsentrasi Asam Asetat Memengaruhi Karakteristik Fisikokimia Pati Sagu Ihur Terasetilasi,” *Jurnal Teknologi dan Industri Pangan*, vol. 31, no. 2, pp. 180–187, 2020, doi: 10.6066/jtip.2020.31.2.180.
- [88] W. H. Chen *et al.*, “Hygroscopic transformation of woody biomass torrefaction for carbon storage,” *Appl Energy*, vol. 231, no. September, pp. 768–776, 2018, doi: 10.1016/j.apenergy.2018.09.135.

- [89] A. Garcia-Maraver, D. Salvachúa, M. J. Martínez, L. F. Diaz, and M. Zamorano, "Analysis of the relation between the cellulose, hemicellulose and lignin content and the thermal behavior of residual biomass from olive trees," *Waste Management*, vol. 33, no. 11, pp. 2245–2249, Nov. 2013, doi: 10.1016/j.wasman.2013.07.010.
- [90] P. Gao *et al.*, "Preparation and characterization of hydrochar from waste eucalyptus bark by hydrothermal carbonization," *Energy*, vol. 97, pp. 238–245, Feb. 2016, doi: 10.1016/j.energy.2015.12.123.